

**RZR PRO R / PRO XP / TURBO R REAR SEAT MOUNTS FOR SPARCO SEATS**

IMPORTANT: Thank you for purchasing this Cagewrx product. Please read through this entire document before proceeding with installation. If you are not confident in your mechanical skills, please seek the help of a professional to perform the installation. Check your packages immediately upon arrival to ensure that everything listed is included, and to check for damage during shipping. If anything is missing or damaged, or if you need technical assistance with any aspect of this installation, call Cagewrx at (951) 223-9118 as soon as possible. This document last updated Nov. 2022.

APPLICATIONS

These Installation Instructions apply to the following Cagewrx products:



RZRPROSM-REAR

RZR PRO Rear Seat Mounts

PARTS LIST

Please check your packages immediately upon arrival to ensure that everything listed is included, and to check for damage during shipping. If anything is missing or damaged, call Cagewrx at (951) 223-9118 as soon as possible.

1. (2) Seat Mount Rails
2. Driver Side Seat Bracket
3. Passenger Side Seat Bracket
4. (2) 5/16" Wire-Lock Clevis Pins
5. (8) 1/4"-20 Carriage Bolts
6. (8) 1/4" SAE Washers
7. (8) 1/4"-20 Nyloc Nuts
8. (4) M8x20 Socket Head Cap Screws
9. (4) 5/16" SAE Washers

TOOLS NEEDED

- Ratchet
- 7/16" Socket
- 6mm Hex Key
- 5/16" Drill Bit
- Power Drill

MUST UPGRADE HARNESSSES!!

You WILL NOT be able to use your stock RZR harnesses with Sparco Seats and Cagewrx Seat Mounts. You will need aftermarket harnesses with separate lap belt and shoulder straps to be able to use the quick release feature. We recommend upgrading to Sparco Camlock harnesses for added safety and proper functionality.

INSTALLATION PROCEDURE

1. Install the Side Brackets using the supplied 1/4"-20 Carriage Bolts, Washers, and Nyloc Nuts. Make sure the slotted holes on the sides of the brackets are toward about the front of the RZR. Also be sure that the square holes in the bases are facing the front on the same end as the slotted holes on the side brackets. Using your 7/16" socket, get these bolts just snug enough to where they still have movement to adjust. You will need to install the front carriage bolt from the bottom with the nyloc nut on the top.



2. Install the Seat Bases with Side Brackets attached to your Sparco Seats using the supplied M8x20 Socket Head Cap Screws and 5/16" washers. There are 4 rear holes and 4 front holes to adjust the height and angle of your seat. We recommend starting at the very bottom hole in the rear and the second hole from the bottom in the front and make adjustments from there.



3. Use a 5/16" Drill Bit to drill out the holes in the factory seat base where you removed the pin to remove the seat.



4. Install your Sparco Seats with your Cagewrx Seat Mounts installed into the rear of your RZR. You will slide the rear slots into the RZR first and then drop the front down into place.



5. Adjust Side Brackets to fit perfectly to the seat once the bases are properly installed in the channels of your RZR. Use your 7/16" socket to fully tighten down the side brackets to the seat bases.

6. Install the provided 5/16" Clevis Pin through the hole in the front of your Cagewrx Seat Mount Bases to secure them to the RZR. Be sure to latch the opposite end to secure the clevis.



7. To remove your Sparco Seat, pull the (2) Clevis Pins in your Cagewrx seat mounts. Pull up on the front of the seat and slide the back of the seat mounts forward and up.

